



DIMENSIONAL DATA:

CASE LENGTH	DIMENSION "A"	DIMENSION "B"	DIMENSION "C"	DIMENSION "D"	NO. HOT WELLS (IF APPLICABLE)
4 FOOT	5' - 9"	2' - 7-1/4"	4' - 0"	4' - 3-1/4"	4 - ZONES
6 FOOT	5' - 9"	2' - 7-1/4"	6' - 0"	6' - 3-1/4"	6 - ZONES
8 FOOT	5' - 9"	2' - 7-1/4"	8' - 0"	8' - 3-1/4"	8 - ZONES
12 FOOT	5' - 9"	2' - 7-1/4"	12' - 0"	12' - 3-1/4"	12 - ZONES

ELECTRICAL DATA:

CASE LENGTH	VOLTAGE	PHASE	AMPS	TOTAL LOAD (Kw)	BREAKER	TERMINATION	PLUG TYPE	CORD PROVIDED Y/N	UL LISTED Y/N
4 FOOT	120/ 208V-5 WIRE	3 PHASE	11.90	4.30	20 AMP		N/A	N	Y
6 FOOT	120/208V-5 WIRE	3 PHASE	23.80	8.50	30 AMP		N/A	N	Y
8 FOOT	120/208V -5 WIRE	3 PHASE	23.90	8.60	30 AMP		N/A	N	Y
12 FOOT	120/208V-5 WIRE	3 PHASE	35.90	12.90	50 AMP		N/A	N	Y

NOTES:

NOTE: ELECTRICAL IS DIRECT CONNECTION HARD WIRED (NO ELECTRICAL CORD)

NOTE: 5 WIRE SERVICE (3 - HOTS, 1 - NEUTRAL, 1 - GROUND)

NOTE: ALL ZONES ARE DIGITALLY CONTROLLED THROUGH ADVANCED COMPUTER TECHNOLOGY TO INSURE AND MAINTAIN PRODUCT TEMPERATURE AND QUALITY.

RH0124.000_NARROW SELF-SERVICE

ARCH	MECH	ELEC	REFR	MECH CONST	OWNER
REVIEWED	REVIEWED	REVIEWED	REVIEWED	V-APR	V-APR

5/1/2014

PDSMT# 10/31/14